

PE ROPE

Suitable for many purposes. It has low surface friction and repels dirt and is good in abrasion. Density is low and it floats.



Part no. Vörunr. Vare nr. Parte no. № изд.	Diameter Þvermál Diámetro Диаметр	Length Lengd Længde Largo Длина	Weight Þyngd Vægt Peso Вес	Breaking strength Slitþol Brudstyrke Resistencia a la rotura Разрывная нагрузка	
GREEN	mm	m	kg/coil	ton	kN
2270070	14	220	21,0	3,1	30
2270080	16	220	28,0	3,8	37
2270090	18	220	35,0	4,3	42
2270100	20	220	44,0	4,9	48
2270110	24	220	59,0	7,5	74
2270135	28	110	43,0	9,6	94
RED					
2270113	24	110	29,5	7,5	74
2270130	28	110	43,0	9,6	94
2270140	32	110	56,0	11,8	116
YELLOW					
2270112	24	110	29,5	7,5	74
2270132	28	110	43,0	9,6	94
BLUE					
2270114	24	110	29,5	7,5	74
2270134	28	110	43,0	9,6	94

▶ PE ROPE

3 strand twisted.

▶ PE FÆRATÓG

3 þátta snúið.

▶ PE TOV

3 slâet.

▶ PE CUERDA

3 cabos retorcidos.

▶ PE ВЕРЕВКА

3-прядный
крученный.

Properties	
Material	Polyethylene
Construction	3 strand twisted
Elongation	23%
Colour	Green Red Yellow Blue
Marker	Yellow in green rope
Density	0,96
Melting point	140°C
Water uptake	0%
UV resistance	Good
Abrasion resistance	Good

